

## CO70

### Contact Oil

#### DESCRIPTION

**CO70** Contact Oil has been developed to offer exceptional performance at low temperatures (down to -55 °C). It is ideal for use on contacts with low contact pressures and in applications where it will not migrate, for example brushes, bearings, jack plugs, push button switches, relays etc. It is also suitable for lubricating slip ring and slip disc contacts.

READ ENTIRE TECHNICAL BULLETIN BEFORE USING THIS PRODUCT

#### FEATURES AND BENEFITS

- Exceptional performance at low temperatures; can be used down to -55 °C
- Good plastics compatibility; suitable with some sensitive plastics, testing is always advised
- Produces low and constant mV drop and contact resistance; ensures reliability of the contact
- Grease version available, CG70; for use on surfaces where an oil may migrate

#### APPROVALS

Standard	Status
RoHS Compliant (2015/863/EU)	Yes

#### PRODUCT INFORMATION

For available packaging sizes please visit:

[electrolube.com](http://electrolube.com)

### PHYSICAL PROPERTIES

Category	Results
<b>Typical Properties</b>	
Appearance	Colorless Liquid
Base	Blend of Synthetic Fluids
Density @ 20 °C (ASTM D1298 (g/mL))	0.85
Kenematic Viscosity (mm <sup>2</sup> /s)	
20 °C	44
40 °C	22
Operating Temperature Range (°C)	-55 to 130
Copper Corrosion; 4 hours @ 150 °C (DIN 51759/IP112)	Class 1a
Silver Corrosion 3 hours @ 100 °C (DIN 51759)	No Color Change
Pour Point (°C)	-70
Flash Point (°C)	>220
<b>Mechanical Properties</b>	
4 Ball Wear (mm)	2.895
Weld Load (kgf)	126

### APPLICATION GUIDELINES

Before final treatment with our lubricants, contact surfaces should be clean and dry. For general removal of dirt, our Ultrasolve is recommended. Hardened dirt and tarnish, especially on larger contacts, should be removed by rubbing with an abrasive material, which can be impregnated with the lubricant to be used.

After cleaning non-wiping contacts, loosened tarnish should be removed before a final application of lubricant is made. Contact Cleaning Strips (CCS) are recommended for this purpose. With wiping contacts, loosened tarnish will be pushed aside. This can be removed if desired, but is usually not necessary, due to the excellent lubricating and protective properties of the contact lubricant.

CO70 can be applied by one of the following methods (although this list is not exhaustive):

- Manually** by way of a syringe/dropper bottle
- Semi-automated** using syringe dispensing
- Fully automated** by way of a dispensing system

### TYPICAL PRODUCT APPLICATION

CO70 is ideal for use on contacts with low contact pressures and in applications where it will not migrate, for example brushes, bearings, jack plugs, push button switches, relays etc. It is also suitable for lubricating slipring and slipdisc contacts.

### ADDITIONAL INFORMATION

**Shelf Life:** 36 Months

### SAFETY & WARNING

It is recommended that the company/operator read and review the Safety Data Sheets for the appropriate health and safety warnings before use. **Safety Data Sheets are available.**

### CONTACT INFORMATION

To confirm this document is the most recent version, please contact

**TechnicalSupportTeam@hkw.co.uk**

[www.electrolube.com](http://www.electrolube.com)

<b>North America</b> 109 Corporate Blvd. South Plainfield, NJ 07080, USA 1.800.367.5460	<b>Europe</b> Ashby Park Coalfield Way Ashby de la Zouch Leicestershire, LE65 1JR, UK 44.01530.41960	<b>Asia</b> 8/F., Paul Y. Centre 51 Hung To Road Kwun Tong, Kowloon, Hong Kong 852.3190.3100
--	---	--

Also read carefully warning and safety information on the Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product. READ IT THOROUGHLY PRIOR TO PRODUCT USE. Emergency safety directory assistance: US 1 202 464 2554, Europe + 44 1235 239 670, Asia + 65 3158 1074, Brazil 0800 707 7022 and 0800 172 020, Mexico 01800 002 1400 and (55) 5559 1588

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any noncompliant product at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct, indirect, incidental or consequential, arising out of the inability to use the product. Notwithstanding the foregoing, if products are supplied in response to a customer request that specifies operating parameters beyond those stated above, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product failure and of all direct, indirect, incidental and consequential damages that may result from use of the products under such conditions, and agrees to exonerate, indemnify, defend and hold harmless MacDermid, Incorporated and its affiliates therefrom. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in a manner that infringes any patent or other intellectual property rights, and seller and manufacturer assume no responsibility or liability for any such infringement.

© 2019 MacDermid, Inc. and its group of companies. All rights reserved. "R" and "TM" are registered trademarks or trademarks of MacDermid, Inc. and its group of companies in the United States and/or other countries.