

## LFFR

### Lead Free Flux Remover

#### DESCRIPTION

**LFFR** is a fast-drying solvent cleaner specially formulated for the quick and efficient removal of lead free flux residues. **LFFR** will remove R, RA, RMA and No-Clean flux residues associated with both lead-free and tin/lead soldering products.

READ ENTIRE TECHNICAL BULLETIN BEFORE USING THIS PRODUCT

#### FEATURES AND BENEFITS

- Removes a wide range of lead-free flux residues; ideal for manual PCB cleaning applications
- Non-halogenated cleaning solvent; will not attack the ozone layer
- Dries without leaving any residue; leaves a clean, dry surface in one cleaning step
- Brush aerosol version available; for more stubborn deposits

#### APPROVALS

| Standard                     | Status |
|------------------------------|--------|
| RoHS Compliant (2015/863/EU) | Yes    |

#### PRODUCT INFORMATION

For available packaging sizes please visit:

[electrolube.com](http://electrolube.com)

### PHYSICAL PROPERTIES

| Category                     | Results                          |
|------------------------------|----------------------------------|
| <b>Typical Properties</b>    |                                  |
| Form                         | Colorless liquid with lemon odor |
| Density @ 20 °C (g/mL)       | 0.78                             |
| Boiling Point (°C)           | >80                              |
| Flash Point (°C)             | 0                                |
| Vapor Pressure (kPa)         | 11.5                             |
| Inhalation Toxicity (ppm)    | 300                              |
| Residue on Evaporation (ppm) | <1                               |
| Evaporation Rate             | 16 (ether = 1)                   |

### APPLICATION GUIDELINES

Suitable for removal of a range of flux residues after soldering. Spray onto surface to be cleaned and use integral brush to aid removal of stubborn deposits. Sensitive plastics should be tested prior to use. Product contains flammable solvent so do not spray onto live electrical equipment or other sources of ignition.

### ADDITIONAL INFORMATION

**Shelf Life:** 36 Months

### SAFETY & WARNING

It is recommended that the company/operator read and review the Safety Data Sheets for the appropriate health and safety warnings before use. **Safety Data Sheets are available.**

### CONTACT INFORMATION

To confirm this document is the most recent version, please contact

**TechnicalSupportTeam@hkw.co.uk**

[www.electrolube.com](http://www.electrolube.com)

|  |   |  |
|--|---|--|
| <b>North America</b><br>109 Corporate Blvd.<br>South Plainfield, NJ 07080, USA<br>1.800.367.5460 | <b>Europe</b><br>Ashby Park<br>Coalfield Way<br>Ashby de la Zouch<br>Leicestershire, LE65 1JR, UK<br>44.01530.41960 | <b>Asia</b><br>8/F., Paul Y. Centre<br>51 Hung To Road<br>Kwun Tong, Kowloon, Hong Kong<br>852.3190.3100 |
|--|---|--|

Also read carefully warning and safety information on the Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product. READ IT THOROUGHLY PRIOR TO PRODUCT USE . Emergency safety directory assistance: US 1 202 464 2554, Europe + 44 1235 239 670, Asia + 65 3158 1074, Brazil 0800 707 7022 and 0800 172 020, Mexico 01800 002 1400 and (55) 5559 1588

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any noncompliant product at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct, indirect, incidental or consequential, arising out of the inability to use the product. Notwithstanding the foregoing, if products are supplied in response to a customer request that specifies operating parameters beyond those stated above, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product failure and of all direct, indirect, incidental and consequential damages that may result from use of the products under such conditions, and agrees to exonerate, indemnify, defend and hold harmless MacDermid, Incorporated and its affiliates therefrom. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in a manner that infringes any patent or other intellectual property rights, and seller and manufacturer assume no responsibility or liability for any such infringement.

© 2019 MacDermid, Inc. and its group of companies. All rights reserved. "(R)" and "TM" are registered trademarks or trademarks of MacDermid, Inc. and its group of companies in the United States and/or other countries.