

SMFL/SMF

Surface Mount Rework Flux

DESCRIPTION

SMFL is a quick drying, mildly activated (RMA-type), no-clean flux in aerosol form for use when removing and replacing surface mount components. The aerosol is fitted with a wide angle actuator to give a protective film and an extension tube actuator for pinpoint application. Particularly recommended for precision products e.g., telecommunications or professional computers where a high degree of reliability is required.

READ ENTIRE TECHNICAL BULLETIN BEFORE USING THIS PRODUCT

FEATURES AND BENEFITS

- Available in CO₂ propelled aerosol and pen type dispensers
- · Zero halide content; no cleaning of residues is required
- Passes copper plate and copper mirror corrosion (residue) test
- For use with hot air, hot gas or conventional soldering techniques; excellent solderability

PRODUCT INFORMATION

For available packaging sizes please visit:

electrolube.com





PHYSICAL PROPERTIES

Category	Results
Typical Properties	
Flux Type	Mildly activated resin (RMA)
Color	Pale Straw
Flash Point (°C)	12
Drying Times	5 to 10 minutes at room temperature
Halide Content	0
Non-Volatile Content	18%

APPLICATION GUIDELINES

Application of SMFL to solder joints will aid reflow when heating to remove components.

After removing components excess solder should be removed from solder pads using our desolder braid aided by the application of SMFL.

SMFL should be applied to solder pads for placement of new components, with hot air or hot gas, or using conventional solder and iron.

SMFL can also be used as an anti-tarnish, protective film on bare copper or tinned tracks providing excellent solderability for up to six months.

ADDITIONAL INFORMATION

Shelf Life

0.1011 =0	
Description	Shelf Life
Pen	24 Months
Aerosol	36 Months



TECHNICAL BULLETIN

SAFETY & WARNING

It is recommended that the company/operator read and review the Safety Data Sheets for the appropriate health and safety warnings before use. **Safety Data Sheets are available.**

CONTACT INFORMATION

To confirm this document is the most recent version, please contact TechnicalSupportTeam@hkw.co.uk

www.electrolube.com

North America 109 Corporate Blvd. South Plainfield, NJ 07080, USA 1.800.367.5460 Europe
Ashby Park
Coalfield Way
Ashby de la Zouch
Leicestershire, LE65 1JR, UK
44.01530.41960

Asia 8/F., Paul Y. Centre 51 Hung To Road Kwun Tong, Kowloon, Hong Kong 852.3190.3100

Also read carefully warning and safety information on the Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product. READ IT THOROUGHLY PRIOR TO PRODUCT USE . Emergency safety directory assistance: US 1 202 464 2554, Europe + 44 1235 239 670, Asia + 65 3158 1074, Brazil 0800 707 7022 and 0800 172 020, Mexico 01800 002 1400 and (55) 5559 1588

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any noncompliant product at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct, indirect, incidental or consequential, arising out of the inability to use the product. Notwithstanding the foregoing, if products are supplied in response to a customer request that specifies operating parameters beyond those stated above, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product failure and of all direct, indirect, incidental and consequential damages that may result from use of the products under such conditions, and agrees to exonerate, indemnify, defend and hold harmless MacDemnid, Incorporated and its affiliates therefrom. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in a manner that infringes any patent or other intellectual property rights, and seller and manufacturer assume no responsibility or liability for any such infringement.

© 2019 MacDermid, Inc. and its group of companies. All rights reserved. "(R)" and "TM" are registered trademarks or trademarks of MacDermid, Inc. and its group of companies in the United States and/or other countries.

